



Star8000F Multi-parameters Monitor

General Specification

Configuration

Standard: 3/5-lead ECG, RESP, SpO2, PR, NIBP

Optional: IBP, Temp2, CO2, Masimo SpO2, Nellcor SpO2

Power Supply

AC input voltage: 100-240V~, 50/60Hz

Built-in battery (Standard) : 2200mAh, at least 2 consecutive hours.

Built-in battery (Optional) : 4400mAh, at least 4 consecutive hours.

Display

Dimension: About 300mm×155mm×278mm

Weight: about 2.72kg (without battery)

Display: 12.1 Inch touch screen

Waveforms: Maximum 8 waveforms display

Resolution: 800×600

Environmental Specifications

Environment temperature: 5℃ ~ 40℃

Relative humidity: ≤93%

Atmospheric pressure: 700hPa ~ 1060hPa

Indicator

Dual alarm indicator lights, Power indicator light,
Battery indicator light, QRS beep and alarm sound,
Operating key sound

External interface

Parameter cable interface, AC power input socket, USB port

RJ45 port, Multifunction port, Equipotential jack, Wall-mounted rack

Data Review and Storage

Trend table/graph: 160hrs

Full disclosure waveform: 48h

Power-off Protection

NIBP storage: 2000 groups

Alarm storage: 200

ECG Specifications

Lead type: 3-lead, 5-lead or 12-lead selectable

Lead selection:

3-lead (I, II, III), 1-channel

5-lead (I, II, III, avR, avL, avF, V), 2-channel

12-lead (R, L, F, N, C1, C2, C3, C4, C5, C6 or RA, LA, LL, RL, V1, V2, V3, V4, V5, V6); 2-channel

HR measurement range:

Adult: 15~300bpm

Neonate/child: 15~350bpm

Accuracy: ±1% or ±1bpm, whichever is greater.

ST measurement range: 2.0mV+2.0mV (-20.0 mm~+20.0 mm)

Arrhythmia: 26 calls

Waveform speed: 6.25mm/s, 12.5mm/s, 25 mm/s, 50 mm/s

Gain selection: 1.25, 2.5, 5.0, 10, 20, 40mm/mV, Auto.

Pacemaker detection: Yes

Protection: Against electrosurgical interference and defibrillation.

Bandwidth:

Surgery mode: 1 Hz ~ 20 Hz (-3.0dB ~ +0.4dB);

Monitoring Mode: 0.5 Hz ~ 40 Hz (-3.0dB ~ +0.4dB);

Diagnosis mode: 0.05Hz ~ 150 Hz (-3.0dB ~ +0.4dB);

ST mode: 0.05Hz ~ 40Hz (-3.0dB ~ +0.4dB)

ECG analog output

Common mode rejection: <1mV (p-v RTI)

Non-invasive Blood Pressure(NIBP)

Method: Auto oscillation method

Parameters: SYS/DIA/MAP/Pulse Rate

Operating mode: Manual/Auto/STAT

Auto measure intervals: 1/2/2.5/3/4/5/10/15/30/60/
90/120/180/240/480/720min

Units: mmHg/kPa

Cuff pressure range: Adult: 80 ~ 280;

Child: 80 ~ 210;

Neonate: 60 ~ 140

Measurement and alarm range:

SYS: (adult) 5.3-36kPa (40-270mmHg)
(Child) 5.3-26.7kPa (40-200mmHg)
(Neonate) 5.3-18kPa (40-135mmHg)
DIA: (adult) 1.3-28.7kPa (10-215mmHg)
(Child) 1.3-20kPa (10-150mmHg)
(Neonate) 1.3-13.3kPa (10-100mmHg)
MEAN: (adult) 2.7-31.3kPa (20-235mmHg)
(Child) 2.7-22kPa (20-165mmHg)
Accuracy: ± 0.1 kPa or ± 1 mmHg, whichever is greater.
PR measurement range: 40 bpm - 240 bmp
Accuracy: ± 2 bpm or $\pm 2\%$, whichever is greater
Over-pressure protection: Yes

Resp Specifications :

Measurement method: Thoracic impedance
Measurement range: Adult: 0 - 120 rpm
Child/neonate: 0rpm-150rpm
Accuracy: 7rpm~150rpm: ± 2 rpm or $\pm 2\%$, whichever is greater.
0rpm~6rpm: not defined.
No breath alarm delay: 10s、15s、20s、25s、30s、35s、40s、45s、50s、55s、1min、Off

SpO2 Specifications

Measurement range & Accuracy:

Comen SpO2:

0%~100%;

accuracy:

$\pm 2\%$ (adult/child, in non-motion state) or
 $\pm 3\%$ (neonate, in non-motion state) within
the measurement range of 70%~100%.

Masimo SpO2:

1%~100%;

accuracy:

$\pm 2\%$ (adult/child, in non-motion state),
 $\pm 3\%$ (adult/child, in motion state) or
 $\pm 3\%$ (neonate, in motion or non-motion state)
within the measurement range of 70%~100%.

Nellcor SpO2:

0%~100%;

accuracy:

$\pm 2\%$ (adult/child, in non-motion state) or
 $\pm 3\%$ (neonate, in non-motion state) within
the measurement range of 70%~100%.

The measurement accuracy within the measurement range of 1%~69% is not defined.

Perfusion index (PI):

Range for Masimo SpO2 and Comen SpO2: 0.02%~20%;

accuracy: not defined.

Resolution:

0.01% (within 0.02%~9.99% range)
or 0.1% (within 10.0%~20.0% range).

PR Specifications

Measurement range and accuracy:

Comen SpO2: 20bpm~254bpm; resolution: 1bpm;

Masimo SpO2: 25bpm~240bpm; resolution: 1bpm;

Nellcor SpO2: 20bpm~300bpm; resolution:1bpm;

Temp Specifications

Measurement range: 0℃~50℃

Accuracy: ± 0.1 ℃

Number of channels: 2

CO2 Specifications

Masimo EtCO2 sensor (mainstream):

CO2 measurement range:

0mmHg~190mmHg, 0~25% (at 760mmHg)

CO2 resolution: 1mmHg, 0.1kPa or 0.1%

CO2 accuracy: 0~15%: $\pm(0.2\%+\text{reading}\times 2\%)$

15~25%: not defined

Masimo EtCO2 sensor (sidestream):

CO2 measurement range:

0mmHg~190mmHg, 0~25% (at 760mmHg)

CO2 resolution: 1mmHg, 0.1kPa or 0.1%

CO2 accuracy: 0~15%: $\pm(0.2\%+\text{reading}\times 2\%)$

15~25%: not defined

Respironics/Nmed/Palconn EtCO2 sensor (mainstream)

CO2 measurement range:

0~150mmHg 0%~19.7% (0~20.0kPa)

CO2 resolution: 0~69mmHg: 0.1mmHg

70~150mmHg: 0.25mmHg

CO2 accuracy: 0~40mmHg: ± 2 mmHg

41~70mmHg: $\pm 5\%\times \text{reading}$

71~100mmHg: $\pm 8\%\times \text{reading}$

101~150mmHg: $\pm 10\%\times \text{reading}$

Respironics/Nmed/Palconn EtCO2 sensor (side stream)

CO2 measurement range:

0~150mmHg 0%~19.7% (0~20.0kPa)

CO2 resolution: 0~69mmHg: 0.1mmHg

70~150mmHg: 0.25mmHg

CO2 accuracy: 0~40mmHg: ± 2 mmHg

41~70mmHg: $\pm 5\%\times \text{reading}$

71~100mmHg: $\pm 8\%\times \text{reading}$

101~150mmHg: $\pm 10\%\times \text{reading}$

IBP Specifications

Channels: 2

Measurement range: -1.3kPa~+40kPa(-50mmHg~+300mmHg)

Resolution: 0.1kPa or 1mmHg

Accuracy: ± 1 mmHg or $\pm 2\%$, whichever is greater .

Recording Specifications

Recording paper width: 50mm

Paper speed: 25/50 mm/s

Number of waveforms: 3

Specifications subject to change without notice

Shenzhen Comen Medical Instrument Co.,Ltd

Add: No.2 of FIYTA Timepiece Building, Nanhuan Avenue,
Gongming Sub-district,Guangming New District, Shenzhen,
P.R.China

Tel:+86-755-2640 8879 2641 0713

Fax:+86-755-2643 1232

Website: en.comen.com

E-mail: info@szcomen.com

CFDA CE 0120

